

SAFETY DATA SHEET

Page : 1 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Supersedes :

Solve-M Ready Mixed Coolant 50:50



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : D2053 - (50%)
UFI : AV4K-3TGV-4H6U-G473

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Coolant

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

SOLVENTIS EUROPE NV
Sint Maartenstraat 1
2000 Antwerpen - BELGIUM
T +32 3 205 16 66
sds@solventis.net

Other

Solventis Ltd
Compton House,
The Guildway,
Old Portsmouth Road,
Guildford
GU3 1LR Surrey - UK
T +44 1483 203224 - F +44 1483 205040
sds@solventis.net

1.4. Emergency telephone number

Emergency number : +32 (0)3 575 55 55
This telephone number is available 24 hours per day, 7 days per week.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Oral) H302
Eye Irrit. 2 H319
STOT RE 2 H373

Full text of H- and EUH-statements: see section 16

2.2. Label elements

SAFETY DATA SHEET

Page : 2 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

Signal word :

Warning

Hazardous ingredients :

2,2' -OXYBISETHANOL, DIETHYLENE GLYCOL, ethanediol; ethylene glycol

Hazard statements (CLP) :

H302 - Harmful if swallowed.
H319 - Causes serious eye irritation.
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Precautionary statements (CLP) :

P260 - Do not breathe vapours, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTER, doctor if you feel unwell.
P330 - Rinse mouth.
P501 - Dispose of contents and container to a hazardous or special waste collection point.

2.3. Other hazards

Other hazards :

Results of PBT and vPvB assessment : Not applicable.

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethanediol; ethylene glycol substance with a Community workplace exposure limit	(CAS-No.) 107-21-1 (EC-No.) 203-473-3 (EC Index) 603-027-00-1 (REACH-no) 01-2119456816-28-xxxx	26,25 – 85,5	Acute Tox. 4 (Oral), H302 STOT RE 2, H373
2,2' -OXYBISETHANOL, DIETHYLENE GLYCOL	(CAS-No.) 111-46-6 (EC-No.) 203-872-2 (EC Index) 603-140-00-6	0 – 13,5	Acute Tox. 4 (Oral), H302

SAFETY DATA SHEET

Page : 3 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



Potassium 2-Ethylhexanoate	(CAS-No.) 3164-85-0 (EC-No.) 221-625-7 (EC Index) - (REACH-no) 01-2119980714-29-xxxx	0,35 – 2,7	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361d
----------------------------	---	------------	---

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.
Inhalation	: Remove casualty to fresh air and keep warm and at rest. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Remove contaminated clothing and shoes. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: May cause irritation to the respiratory tract. The following symptoms may occur: Cough. Dizziness. Headache.
Skin contact	: May cause skin irritation. May be absorbed through the skin. Repeated exposure may cause skin dryness or cracking.
Eyes contact	: Causes serious eye irritation. The following symptoms may occur: Redness, pain.
Ingestion	: Harmful if swallowed. The following symptoms may occur: Vomiting. Weakness. Unconsciousness. Abdominal pain. Nausea.
Chronic symptoms	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO ₂), powder, alcohol-resistant foam, water spray.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards	: Not flammable. Heating will cause a rise in pressure with a risk of bursting.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
---------------------------	---

SAFETY DATA SHEET

Page : 4 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
- Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

6.1.2. For emergency responders

- For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

- Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

- Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures

- : Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.

SAFETY DATA SHEET

Page : 5 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



SOLVENTIS MARINE COOLANTS

- Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Special rules on packaging : Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep container tight closed.
- Packaging materials : Keep only in the original container.

7.3. Specific end use(s)

Coolant.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

2,2' -OXYBISETHANOL, DIETHYLENE GLYCOL (111-46-6)		
Austria	MAK (OEL TWA)	44 mg/m ³
Austria	MAK (OEL TWA) [ppm]	10 ppm
Austria	MAK (OEL STEL)	176 mg/m ³
Austria	MAK (OEL STEL) [ppm]	40 ppm
Bulgaria	OEL TWA	10 mg/m ³
Croatia	GVI (OEL TWA) [1]	101 mg/m ³
Croatia	GVI (OEL TWA) [2]	23 ppm
Denmark	OEL TWA [1]	11 mg/m ³
Denmark	OEL TWA [2]	2,5 ppm
Estonia	OEL TWA	45 mg/m ³
Estonia	OEL TWA [ppm]	10 ppm
Estonia	OEL STEL	90 mg/m ³
Estonia	OEL STEL [ppm]	20 ppm
Germany	Occupational exposure limit value (mg/m ³) (TRGS900)	44 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	Occupational exposure limit value (ppm) (TRGS900)	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Ireland	OEL TWA [1]	100 mg/m ³
Ireland	OEL TWA [2]	23 ppm
Ireland	OEL STEL	300 mg/m ³ (calculated)
Ireland	OEL STEL [ppm]	69 ppm (calculated)
Latvia	OEL TWA	10 mg/m ³
Lithuania	IPRV (OEL TWA)	45 mg/m ³ (2,2-Oxydiethanol)
Lithuania	IPRV (OEL TWA) [ppm]	10 ppm (2,2-Oxydiethanol)
Lithuania	TPRV (OEL STEL)	90 mg/m ³ (2,2-Oxydiethanol)
Lithuania	TPRV (OEL STEL) [ppm]	20 ppm (2,2-Oxydiethanol)
Poland	NDS (OEL TWA)	10 mg/m ³ (inhalable fraction)
Romania	OEL TWA	500 mg/m ³

SAFETY DATA SHEET

Page : 6 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :

**2,2' -OXYBISETHANOL, DIETHYLENE GLYCOL (111-46-6)**

Romania	OEL TWA [ppm]	115 ppm
Romania	OEL STEL	800 mg/m ³
Romania	OEL STEL [ppm]	184 ppm
Slovakia	NPHV (OEL TWA) [1]	44 mg/m ³
Slovakia	NPHV (OEL TWA) [2]	10 ppm
Slovakia	NPHV (OEL C)	90 mg/m ³
Slovenia	OEL TWA	44 mg/m ³
Slovenia	OEL TWA [ppm]	10 ppm
Slovenia	OEL STEL	176 mg/m ³
Slovenia	OEL STEL [ppm]	40 ppm
Sweden	NGV (OEL TWA)	45 mg/m ³
Sweden	NGV (OEL TWA) [ppm]	10 ppm
Sweden	KTV (OEL STEL)	90 mg/m ³
Sweden	KTV (OEL STEL) [ppm]	20 ppm
United Kingdom	WEL TWA (OEL TWA) [1]	101 mg/m ³
United Kingdom	WEL TWA (OEL TWA) [2]	23 ppm
United Kingdom	WEL STEL (OEL STEL)	303 mg/m ³ (calculated)
United Kingdom	WEL STEL (OEL STEL) [ppm]	69 ppm (calculated)
Switzerland	MAK (OEL TWA) [1]	44 mg/m ³ (aerosol, vapour)
Switzerland	MAK (OEL TWA) [2]	10 ppm (aerosol, vapour)
Switzerland	KZGW (OEL STEL)	176 mg/m ³ (aerosol, vapour)
Switzerland	KZGW (OEL STEL) [ppm]	40 ppm (aerosol, vapour)
Australia	OES TWA [1]	100 mg/m ³
Australia	OES TWA [2]	23 ppm

ethanediol; ethylene glycol (107-21-1)

EU	IOEL TWA	52 mg/m ³
EU	IOEL TWA [ppm]	20 ppm
EU	IOEL STEL	104 mg/m ³
EU	IOEL STEL [ppm]	40 ppm
EU	Remark	Possibility of significant uptake through the skin
Austria	MAK (OEL TWA)	26 mg/m ³
Austria	MAK (OEL TWA) [ppm]	10 ppm
Austria	MAK (OEL STEL)	52 mg/m ³
Austria	MAK (OEL STEL) [ppm]	20 ppm
Bulgaria	OEL TWA	52 mg/m ³
Bulgaria	OEL TWA [ppm]	20 ppm
Bulgaria	OEL STEL	104 mg/m ³
Bulgaria	OEL STEL [ppm]	40 ppm
Croatia	GVI (OEL TWA) [1]	52 mg/m ³
Croatia	GVI (OEL TWA) [2]	20 ppm

SAFETY DATA SHEET

Page : 7 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



ethanediol; ethylene glycol (107-21-1)		
Croatia	KGVI (OEL STEL)	104 mg/m ³
Croatia	KGVI (OEL STEL) [ppm]	40 ppm
Cyprus	OEL TWA	52 mg/m ³
Cyprus	OEL TWA [ppm]	20 ppm
Cyprus	OEL STEL	104 mg/m ³
Cyprus	OEL STEL [ppm]	40 ppm
Czech Republic	PEL (OEL TWA)	50 mg/m ³
Denmark	OEL TWA [1]	26 mg/m ³ 10 mg/m ³ (atomized)
Denmark	OEL TWA [2]	10 ppm
Estonia	OEL TWA	52 mg/m ³ (total concentration of aerosol and vapor)
Estonia	OEL TWA [ppm]	20 ppm (total concentration of aerosol and vapor)
Estonia	OEL STEL	104 mg/m ³ (total concentration of aerosol and vapor)
Estonia	OEL STEL [ppm]	40 ppm (total concentration of aerosol and vapor)
Finland	HTP (OEL TWA) [1]	50 mg/m ³
Finland	HTP (OEL TWA) [2]	20 ppm
Finland	HTP (OEL STEL)	100 mg/m ³
Finland	HTP (OEL STEL) [ppm]	40 ppm
France	VME (OEL TWA)	52 mg/m ³ (indicative limit-vapor)
France	VME (OEL TWA) [ppm]	20 ppm (indicative limit-vapor)
France	VLE (OEL C/STEL)	104 mg/m ³ (indicative limit-vapor)
France	VLE (OEL C/STEL) [ppm]	40 ppm (indicative limit-vapor)
Germany	Occupational exposure limit value (mg/m ³) (TRGS900)	26 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Germany	Occupational exposure limit value (ppm) (TRGS900)	10 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Gibraltar	OEL TWA	52 mg/m ³
Gibraltar	OEL TWA [ppm]	20 ppm
Gibraltar	OEL STEL	104 mg/m ³
Gibraltar	OEL STEL [ppm]	40 ppm
Greece	OEL TWA	125 mg/m ³ (vapor)
Greece	OEL TWA [ppm]	50 ppm (vapor)
Greece	OEL STEL	125 mg/m ³ (vapor)
Greece	OEL STEL [ppm]	50 ppm (vapor)
Hungary	AK (OEL TWA)	52 mg/m ³

SAFETY DATA SHEET

Page : 8 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :

**ethanediol; ethylene glycol (107-21-1)**

Hungary	CK (OEL STEL)	104 mg/m ³
Ireland	OEL TWA [1]	52 mg/m ³
Ireland	OEL TWA [2]	20 ppm
Ireland	OEL STEL	104 mg/m ³
Ireland	OEL STEL [ppm]	40 ppm
Italy	OEL TWA	52 mg/m ³
Italy	OEL TWA [ppm]	20 ppm
Italy	OEL STEL	104 mg/m ³
Italy	OEL STEL [ppm]	40 ppm
Latvia	OEL TWA	52 mg/m ³
Latvia	OEL TWA [ppm]	20 ppm
Lithuania	IPRV (OEL TWA)	25 mg/m ³ (aerosol and vapor)
Lithuania	IPRV (OEL TWA) [ppm]	10 ppm (aerosol and vapor)
Lithuania	TPRV (OEL STEL)	50 mg/m ³ (aerosol and vapor)
Lithuania	TPRV (OEL STEL) [ppm]	20 ppm (aerosol and vapor)
Luxembourg	OEL TWA	52 mg/m ³
Luxembourg	OEL TWA [ppm]	20 ppm
Luxembourg	OEL STEL	104 mg/m ³
Luxembourg	OEL STEL [ppm]	40 ppm
Malta	OEL TWA	52 mg/m ³
Malta	OEL TWA [ppm]	20 ppm
Malta	OEL STEL	104 mg/m ³
Malta	OEL STEL [ppm]	40 ppm
Netherlands	TGG-8u (OEL TWA)	52 mg/m ³ (fume) 10 mg/m ³ (droplets)
Netherlands	TGG-15min (OEL STEL)	104 mg/m ³
Poland	NDS (OEL TWA)	15 mg/m ³
Poland	NDSch (OEL STEL)	50 mg/m ³
Portugal	OEL TWA	52 mg/m ³ (indicative limit value)
Portugal	OEL TWA [ppm]	20 ppm (indicative limit value)
Portugal	OEL STEL	104 mg/m ³ (indicative limit value)
Portugal	OEL STEL [ppm]	40 ppm (indicative limit value)
Portugal	OEL C	100 mg/m ³ (aerosol only)
Romania	OEL TWA	52 mg/m ³
Romania	OEL TWA [ppm]	20 ppm
Romania	OEL STEL	104 mg/m ³
Romania	OEL STEL [ppm]	40 ppm
Slovakia	NPHV (OEL TWA) [1]	52 mg/m ³

SAFETY DATA SHEET

Page : 9 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



ethanediol; ethylene glycol (107-21-1)		
Slovakia	NPHV (OEL TWA) [2]	20 ppm
Slovakia	NPHV (OEL C)	104 mg/m ³
Slovenia	OEL TWA	52 mg/m ³
Slovenia	OEL TWA [ppm]	20 ppm
Slovenia	OEL STEL	104 mg/m ³
Slovenia	OEL STEL [ppm]	40 ppm
Spain	VLA-ED (OEL TWA) [1]	52 mg/m ³ (indicative limit value)
Spain	VLA-ED (OEL TWA) [2]	20 ppm (indicative limit value)
Spain	VLA-EC (OEL STEL)	104 mg/m ³
Spain	VLA-EC (OEL STEL) [ppm]	40 ppm
Sweden	NGV (OEL TWA)	25 mg/m ³ (limit value applies to the combined concentration of vapor and aerosol-aerosol and vapor)
Sweden	NGV (OEL TWA) [ppm]	10 ppm (limit value applies to the combined concentration of vapor and aerosol-aerosol and vapor)
Sweden	KTV (OEL STEL)	104 mg/m ³ (limit value applies to the combined concentration of vapor and aerosol-aerosol and vapor)
Sweden	KTV (OEL STEL) [ppm]	40 ppm (limit value applies to the combined concentration of vapor and aerosol-aerosol and vapor)
United Kingdom	WEL TWA (OEL TWA) [1]	10 mg/m ³ (particulates) 52 mg/m ³ (vapour)
United Kingdom	WEL TWA (OEL TWA) [2]	20 ppm (vapour)
United Kingdom	WEL STEL (OEL STEL)	104 mg/m ³ (vapour) 30 mg/m ³ (calculated-particulate)
United Kingdom	WEL STEL (OEL STEL) [ppm]	40 ppm (vapour)
Norway	Grenseverdi (OEL TWA) [1]	52 mg/m ³ (total sum of gas and particulate matter (aerosol) of the substance-aerosol)
Norway	Grenseverdi (OEL TWA) [2]	20 ppm (total sum of gas and particulate matter (aerosol) of the substance-aerosol)
Norway	Korttidsverdi (OEL STEL)	104 mg/m ³ (total sum of gas and particulate matter (aerosol) of the substance-aerosol)
Norway	Korttidsverdi (OEL STEL) [ppm]	40 ppm (total sum of gas and particulate matter (aerosol) of the substance-aerosol)
Switzerland	MAK (OEL TWA) [1]	26 mg/m ³ (aerosol, vapour)
Switzerland	MAK (OEL TWA) [2]	10 ppm (aerosol, vapour)
Switzerland	KZGW (OEL STEL)	52 mg/m ³ (aerosol, vapour)
Switzerland	KZGW (OEL STEL) [ppm]	20 ppm (aerosol, vapour)
Australia	OES TWA [1]	10 mg/m ³ (particulate) 52 mg/m ³ (vapour)

SAFETY DATA SHEET

Page : 10 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



ethanediol; ethylene glycol (107-21-1)

Australia	OES TWA [2]	20 ppm (vapour)
Australia	OES STEL	104 mg/m ³ (vapour)
Australia	OES STEL [ppm]	40 ppm (vapour)
Canada (Quebec)	Plafond (OEL C)	127 mg/m ³ (mist and vapour)
Canada (Quebec)	Plafond (OEL C) [ppm]	50 ppm (mist and vapour)
USA - ACGIH	ACGIH OEL TWA [ppm]	25 ppm (vapor fraction)
USA - ACGIH	ACGIH OEL STEL	10 mg/m ³ (inhalable particulate matter, aerosol only)
USA - ACGIH	ACGIH OEL STEL [ppm]	50 ppm (vapor fraction)

Additional information : Recommended monitoring procedures : Personal air monitoring. Room air monitoring

8.2. Exposure controls

- Engineering measure(s) : Provide adequate ventilation. Organisational measures to prevent /limit releases, dispersion and exposure. See Section 7 for information on safe handling.
- Personal protective equipment : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
- Hand protection : Wear chemically resistant gloves (tested to EN374) . Suitable material: Nitrile rubber (BTT: >8h, 0,3mm). neoprene gloves (BTT: >8h, 0,3mm). The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
- Eye protection : Use suitable eye protection (EN166): goggles. During splash contact: face shield
- Body protection : Wear suitable protective clothing. Wear suitable coveralls to prevent exposure to the skin
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: (ABEK) (EN 141). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)



Thermal hazard protection : Not required for normal conditions of use. Use dedicated equipment.

Environmental exposure controls : Avoid release to the environment. Comply with applicable Community environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid. slightly. Opaque.
- Colour : Variable or Colourless.

SAFETY DATA SHEET

Page : 11 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Supersedes :

Solve-M Ready Mixed Coolant 50:50



Odour	: mild.
Odour threshold	: No data available
pH	: 7,5 – 9
pH solution	: Neat
Relative evaporation rate (butylacetate=1)	: No data available
Melting / freezing point	: No data available
Freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable, liquid
Vapour pressure	: No data available
Vapour density	: No data available
Relative density	: No data available
Solubility	: Miscible with water.
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: No data available
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.
Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: No data available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SAFETY DATA SHEET

Page : 12 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Supersedes :

Solve-M Ready Mixed Coolant 50:50



SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. See Section 7 for information on safe handling.

10.5. Incompatible materials

Oxidising agents. Strong acids. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

ATE CLP (oral)	514,403 mg/kg bodyweight
----------------	--------------------------

2,2' -OXYBISETHANOL, DIETHYLENE GLYCOL (111-46-6)

LD50/dermal/rabbit	11890 mg/kg
LC50/inhalation/4h/rat	> 4600 mg/m ³ (Exposure time: 4 h)

Potassium 2-Ethylhexanoate (3164-85-0)

LD50/oral/rat	2043 mg/kg (~ OECD 401)
LD50/dermal/rat	> 2000 mg/kg (OECD 402) (24h)

ethanediol; ethylene glycol (107-21-1)

LD50 oral	7712 mg/kg
LD50/dermal/rat	10600 mg/kg
LD50/dermal/rabbit	> 3500 mg/kg
LD50 dermal	10600 mg/kg
LC50/inhalation/4h/rat	> 2,5 mg/l (Exposure time: 6 h)

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: 7,5 – 9

Serious eye damage/irritation : Causes serious eye irritation.
pH: 7,5 – 9

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

SAFETY DATA SHEET

Page : 13 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :

**ethanediol; ethylene glycol (107-21-1)**

NOAEL (chronic, oral, animal/male, 2 years) : 1000 mg/kg bodyweight

NOAEL (chronic, oral, animal/female, 2 years) : 1500 mg/kg bodyweight

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure : May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Potassium 2-Ethylhexanoate (3164-85-0)

NOAEL (oral, rat, 90 days) : 180 mg/kg bodyweight/day mouse

ethanediol; ethylene glycol (107-21-1)

NOAEL (oral, rat, 90 days) : 200 mg/kg bodyweight/day OECD Guideline 407

NOAEL (dermal, rat/rabbit, 90 days) : 2220 mg/kg bodyweight/day OECD 410

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

D2053 - (35-90%)

Kinematic viscosity : No data available

Other adverse effects : May cause damage to organs through prolonged or repeated exposure.
Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

11.2. Information on other hazards**11.2.1. Endocrine disrupting properties**

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2 Other information

Other adverse effects : May cause damage to organs through prolonged or repeated exposure.
Other information : Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

SECTION 12: Ecological information**12.1. Toxicity**

Environmental properties : According to the criteria of the European classification and labelling system, the substance/the product has not to be labelled as "dangerous for the environment".

SAFETY DATA SHEET

Page : 14 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

2,2' -OXYBISETHANOL, DIETHYLENE GLYCOL (111-46-6)	
LC50 - Fish [1]	75200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	84000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Potassium 2-Ethylhexanoate (3164-85-0)	
LC50 - Fish [1]	> 100 mg/l (OECD 203 - Oryzias latipes)
EC50 - Crustacea [1]	106 mg/l (OECD 203) (48h)
EC50 - Crustacea [2]	75 mg/l (OECD 211) (21d)
EC50 72h - Algae [1]	49,3 mg/l (DIN 38412-9 - Desmodesmus)

ethanediol; ethylene glycol (107-21-1)	
LC50 - Fish [1]	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC50 - Fish [2]	14 – 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [1]	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	6500 – 13000 mg/l (Species: Pseudokirchneriella subcapitata)
NOEC (chronic)	15380 mg/l (7d, Pimephales promelas)

12.2. Persistence and degradability

D2053 - (35-90%)	
Persistence and degradability	No additional information available.

Potassium 2-Ethylhexanoate (3164-85-0)	
Persistence and degradability	Readily biodegradable.
Biodegradation	99 % (OECD 301E)

ethanediol; ethylene glycol (107-21-1)	
Persistence and degradability	Readily biodegradable.
Biodegradation	90-100 Experimental data

12.3. Bioaccumulative potential

D2053 - (35-90%)	
Partition coefficient n-octanol/water	No data available
Bioaccumulative potential	No additional information available.

SAFETY DATA SHEET

Page : 15 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Supersedes :

Solve-M Ready Mixed Coolant 50:50



2,2' -OXYBISETHANOL, DIETHYLENE GLYCOL (111-46-6)	
BCF - Fish [1]	100 – 180
Partition coefficient n-octanol/water	-1,98 (at 25 °C)

Potassium 2-Ethylhexanoate (3164-85-0)	
Partition coefficient n-octanol/water (Log Kow)	2,96 (OECD 107)

ethanediol; ethylene glycol (107-21-1)	
Partition coefficient n-octanol/water	-1,93
Bioaccumulative potential	Does not bioaccumulate.

12.4. Mobility in soil

D2053 - (35-90%)	
Mobility in soil	No data available

ethanediol; ethylene glycol (107-21-1)	
Mobility in soil	Not expected to adsorb on soil.

12.5. Results of PBT and vPvB assessment

D2053 - (35-90%)	
Results of PBT assessment	Not applicable

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : Not applicable

12.7. Other adverse effects

Other adverse effects : No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations.

SAFETY DATA SHEET

Page : 16 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :



SOLVENTIS MARINE COOLANTS

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : This material and its container must be disposed of as hazardous waste
 Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities
 The following Waste Codes are only suggestions:
 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

SAFETY DATA SHEET

Page : 17 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Solve-M Ready Mixed Coolant 50:50

Supersedes :

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU-Regulations**

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

D2053 - (35-90%) ; 2,2' -OXYBISETHANOL, DIETHYLENE GLYCOL ; Potassium 2-Ethylhexanoate ; ethanediol; ethylene glycol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations**France**

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
na	Not Applicable	na	na

Germany

Regulatory reference : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

German storage class (LGK) : LGK 12 - Non-combustible liquids

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

Waterbezwaarlijkheid : B (4) - Weinig schadelijk voor in het water levende organismen

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product.
Pregnant/breastfeeding women working with the product must not be in direct contact with the product.

SAFETY DATA SHEET

Page : 18 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Supersedes :

Solve-M Ready Mixed Coolant 50:50



15.2. Chemical safety assessment

Not applicable.

For the following substances of this mixture a chemical safety assessment has been carried outPotassium 2-Ethylhexanoate
ethanediol; ethylene glycol

SECTION 16: Other information

Abbreviations and acronyms:

ABM = Algemene beoordelingsmethodiek
ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods Code
LEL = Lower Explosive Limit/Lower Explosion Limit
UEL = Upper Explosion Limit/Upper Explosive Limit
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
BTT = Breakthrough time (maximum wearing time)
DMEL = Derived Minimal Effect level
DNEL = Derived No Effect Level
EC50 = Median Effective Concentration
EL50 = Median effective level
ErC50 = EC50 in terms of reduction of growth rate
ErL50 = EL50 in terms of reduction of growth rate
EWC = European waste catalogue
LC50 = Median lethal concentration
LD50 = Median lethal dose
LL50 = Median lethal level
NA = Not applicable
NOEC = No observed effect concentration
NOEL: no-observed-effect level
NOELR = No observed effect loading rate
NOAEC = No observed adverse effect concentration
NOAEL = No observed adverse effect level
N.O.S. = Not Otherwise Specified
OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
PNEC = Predicted No Effect Concentration
Quantitative structure-activity relationship (QSAR)
STOT = Specific Target Organ Toxicity
TWA = time weighted average
VOC = Volatile organic compounds
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the datasheet : ECHA (European Chemicals Agency). LOLI. Supplier information.

Training advice : Training staff on good practice. Manipulations are to be done only by qualified and authorised persons.

Other information : Classification - Assessment method: CLP Calculation method (Article 9).

Full text of H- and EUH-statements:

SAFETY DATA SHEET

Page : 19 / 19

Revision nr : 1.0

Issue date : 08/07/2021

Supersedes :

Solve-M Ready Mixed Coolant 50:50

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.